U.S. DEPARTMENT OF COMMERCE
National Technical Information Service
PB-284 107

Regional Air Pollution Study Point and Area Source Organic Emission Inventory

Rockwell International, Creve Coeur, Mo Air Monitoring Center

Prepared for

Environmental Sciences Research Lab, Research Triangle Park, N C

Jun 78

United States
Environmental Protection
Agency

Environmental Sciences Research
Laboratory
Research Triangle Park NC 27711

EPA-600/4-78-028
June 1978

Research and Development

PB 284 107

EPA

Regional Air Pollution Study

Point and Area Source Organic Emission Inventory

REPRODUCED BY
NATIONAL TECHNICAL
INFORMATION SERVICE
U. S. DEPARTMENT OF COMMERCE
SPRINGFIELD, VA. 22161

EPA-600/4-78-028
June 1978

REGIONAL AIR POLLUTION STUDY
Point and Area Source Organic Emission Inventory

by

R. W. Griscom
Rockwell International
Air Monitoring Center
11640 Administration Drive
Creve Coeur, MO 63141

Contract No. 68-02-2093
Task Order 108I

Project Officer

Charles C. Masser
Office of Air Quality Planning and Standards
Office of Air and Water Management
U.S. Environmental Protection Agency
Research Triangle Park, N.C. 27711

ENVIRONMENTAL SCIENCES RESEARCH LABORATORY
OFFICE OF RESEARCH AND DEVELOPMENT
U.S. ENVIRONMENTAL PROTECTION AGENCY
RESEARCH TRIANGLE PARK, N.C. 27711

DISCLAIMER

This report has been reviewed by the Environmental Sciences Research Laboratory, U.S. Environmental Protection Agency, and approved for publication. Approval does not signify that the contents necessarily reflect the views and policies of the U.S. Environmental Protection Agency, nor does mention of trade names or commercial products constitute endorsement or recommendation for use.

ABSTRACT

An inventory of organic emissions from stationary and mobile sources has been assembled for the St. Louis Air Quality Control Region. The inventory covers point and area sources for process, combustion and evaporative emissions.

A breakdown into five categories has been assigned to each source type. The categories are (1) paraffins, (2) olefins, (3) aromatics, (4) aldehydes, and (5) non-reactives. The breakdown was made part of the RAPS Emission Inventory System, which is stored on the EPA's Univac computer at Research Triangle Park, N.C.

CONTENTS

Abstract iii

Tables vi

1.0 Introduction 1

2.0 Total Hydrocarbon Inventory 2

2.1 Point sources 3

2.2 Area sources 7

3.0 Hydrocarbon Classification 9

3.1 Point source inventory 10

3.1.1 Fuel combustion 10

3.1.2 Industrial processes 12

3.2 Area sources 16

4.0 Summary 22

References 24

Appendix

A. RAPS Hydrocarbon Classification for Types of Sources 26

TABLES

Number		Page
1	Total Hydrocarbon Emission Inventory	3
2	Sample of the National Emissions Data System (NEDS) Source Classification Code (SCC) Report	5
3	Sample of Emission Factors	6
4	Hydrocarbon Breakdown--Point Sources	11
5	Coke Oven Gas Analysis	13
6	DuPont Gasoline Analysis	14
7	Average Composition of Gasolines	14
8	Hydrocarbon Breakdown--Area Sources	17
9	Airport Hydrocarbon Emissions	16
10	Composition of Surface Coating Solvents	19
11	Dry Cleaning Hydrocarbon Emissions	20
12	Summary of Total Organic Emissions Inventory by Class	23

1.0 INTRODUCTION

The Regional Air Pollution Study (RAPS) has as its first goal the validation of atmospheric dispersion models. Emissions data, generally supplied in the form of an emission inventory, are a major constituent of a dispersion model. The RAPS Point and Area Source Hydrocarbon Inventory was designed to provide emission data for the evaluations of photochemical reaction models. Since organics participate in photochemical reactions leading to "smog", the inventory includes all available organic emission data. As the reactivity of organics varies widely, it is important to determine not only the amount emitted, but also the composition.

Chemical kinetic mechanisms present in air quality simulation models require some form of hydrocarbon classification in order to treat the reaction processes and rates associated with their structural make-up. One such classification scheme required in using a lumped chemical kinetic reaction mechanism approach distributes hydrocarbons in the atmosphere structurally into paraffin, olefin, aromatic, aldehyde, and non-reactive classes. This report describes how this classification has been determined for hydrocarbon emissions in the St. Louis AQCR and provides sufficient reference data to derive alternative schemes as required.

2.0 TOTAL HYDROCARBON INVENTORY

The basic RAPS Hydrocarbon Inventory is composed of several separate inventories which have been described in various reports.

The hydrocarbon inventory for stationary point sources was developed by Rockwell under Contract No. 68-02-2093, T0108F, and provides an up-to-date listing of hydrocarbon emissions from stationary point sources in the St. Louis AQCR, with a breakdown into methane and non-methane hydrocarbons. The inventory includes all industrial hydrocarbon emission sources which emit more than one ton per year of hydrocarbons. Point sources in the St. Louis Air Quality Control Region (AQCR-70) emit approximately 47,600 tons per year, or 22.6 percent of the hydrocarbon emissions in the AQCR. The report also describes an analytical technique, based on gas chromatography, which is suitable for analysis of hydrocarbons in the concentration range of 1 to 10^6 ppm and is linear with respect to both carbon number and hydrocarbon concentration.

Area source evaporative hydrocarbon emissions from dry cleaning plants, surface coating, and gasoline marketing are included in the "Residential and Commercial Area Sources Emission Inventory" (EPA 450/2-75-078), which provides information on hydrocarbon emissions on a grid square basis. Spatial allocations were based on population and land use densities. Temporal apportioning was based on an 8 AM to 5 PM workday or the diurnal traffic cycle in St. Louis.

Hydrocarbon emissions from small industrial sources are included in the report on "Stationary Industrial Area Sources" (EPA No. 68-02-2093, T0108D). This category contributes only about 110 tons annually, or about 0.05 percent of the total hydrocarbon emissions.

Emissions from mobile sources are the subject of several inventories: The Highway Vehicle Emission Inventory described in EPA 450/3-76-035 and

EPA 450/3-77-019 defines emissions from motor vehicles on a grid square or line basis. Emissions from river vessels are described in "River Towboat Air Pollution in St. Louis" (DOT-TSC-OST-75-42). The "Airport Emission Inventory" (EPA 450/3-75-048) deals with emissions from aircraft. A report on rail operations (EPA 450/3-77-025) describes the methodology and resultant inventory. Emissions from off-highway sources are described in "Off-Highway Mobile Source Emission Inventory" (EPA Contract No. 68-02-2093, TO108E).

A summary of hydrocarbon emissions is shown in Table 1.

TABLE 1. TOTAL HYDROCARBON EMISSION INVENTORY

SOURCE CATEGORY	ANNUAL EMISSIONS, TONS	
Point Sources		
Fuel Combustion	2,717	
Chemical Manufacturing	6,702	
Primary Metals - Coke Ovens	2,339	
Refinery Operations	7,161	
Surface Coatings	21,072	
Petroleum Storage and Marketing	7,457	
Solid Waste Disposal	136	
Miscellaneous	24	
TOTAL		47,610
Area Sources		
Industrial Area Sources	110	
Residential and Commercial	22,610	
Vehicles, Line Sources	100,440	
Vehicles, Area Sources	12,565	
Railroads	4,220	
River Vessels	940	
Airports	1,460	
Off-Highway Mobile	16,280	
Gasoline Marketing	13,650	
Dry Cleaning	645	
Surface Coating	3,757	
TOTAL		176,677
TOTAL, ALL SOURCES		224,287

2.1 POINT SOURCES

Point sources are those individually identified industrial sources which

release emissions through a stack, such as a boiler, or a vent, as in the case of a petroleum storage tank. (Exceptions to this are leaks in refineries from valves, seals, flanges, etc., which are included as point sources under the appropriate SCC numbers.) Point sources in the St. Louis Air Quality Control Region (AQCR) emit approximately 47,600 tons per year total hydrocarbons, or 22.6 percent of the hydrocarbon emissions in the AQCR. The lower cut-off used to define point sources is one ton per year hydrocarbons.

The point source inventory is comprised of data for individual sources in the AQCR for which emissions have been obtained in the course of the RAPS study. Each source is classified by its identification code, called the Source Classification Code (SCC). The SCC is an identification system developed for the National Emissions Data System (NEDS), upon which the point source hierarchy is structured. The SCC system is being used for the RAPS point source data handling system. All data are stored and retrieved by use of the SCC. A process which emits one or more of the criteria air pollutants can be represented by one or several SCC numbers. Table 2 shows a typical sample of SCC numbers. The SCC numbers consist of four groupings. For example, in SCC 4-03-001-02:

Group I - a single digit (4) - designates "Point Source, Evaporative"
Group II - two digits (03) - designates "Petroleum Storage"
Group III - three digits (001) - designates "Fixed Roof"
Group IV - two digits (02) - designates "Breathing-Crude"

In addition, the base unit upon which the emission factors are based is given; in this case, "1000 gallons storage capacity".

The starting point of an emission inventory is data collection. Inventory data such as process, consumption or storage data are gathered. Modeling information is also collected in the form of location and stack parameters. From the inventory data, the appropriate emission factors are obtained and stored in the data file. These factors are based upon the best available information, generally gathered from source tests. The inventory data gathered and emission factors are applied to generate emission figures for total hydrocarbons, as well as other criteria pollutants. Table 3 shows a typical sample of emission factors and the associated SCC numbers.

Reproduced from best available copy.

TABLE 2. SAMPLE OF THE NATIONAL EMISSIONS DATA SYSTEM (NEDS) SOURCE CLASSIFICATION CODE (SCC) REPORT

SCC ID				SCC CATEGORY NAMES				
I	II	III	IV	I	II	III	IV	UNITS
3	90	001	99	INDUSTRIAL PROCESS	INPROCESS FUEL	ANTHRACITE COAL	OTHER/NOT CLASIFD	TONS BURNED
3	90	002	01	INDUSTRIAL PROCESS	INPROCESS FUEL	BITUMINOUS COAL	CEMENT KILN	TONS BURNED
3	90	002	06	INDUSTRIAL PROCESS	INPROCESS FUEL	BITUMINOUS COAL	BRICK KILN/DRY	TONS BURNED
3	90	002	07	INDUSTRIAL PROCESS	INPROCESS FUEL	BITUMINOUS COAL	GYPSUM KILN/ETC	TONS BURNED
3	90	002	08	INDUSTRIAL PROCESS	INPROCESS FUEL	BITUMINOUS COAL	COAL DRYERS	TONS BURNED
3	90	002	99	INDUSTRIAL PROCESS	INPROCESS FUEL	BITUMINOUS COAL	OTHER/NOT CLASIFD	TONS BURNED
3	90	004	01	INDUSTRIAL PROCESS	INPROCESS FUEL	RESIDUAL OIL	ASPHALT DRYER	1000 GALLONS BURNED
3	90	004	02	INDUSTRIAL PROCESS	INPROCESS FUEL	RESIDUAL OIL	CEMENT KILN	1000 GALLONS BURNED
3	90	004	03	INDUSTRIAL PROCESS	INPROCESS FUEL	RESIDUAL OIL	LIME KILN	1000 GALLONS BURNED
3	90	004	04	INDUSTRIAL PROCESS	INPROCESS FUEL	RESIDUAL OIL	KAOLIN KILN	1000 GALLONS BURNED
3	90	004	05	INDUSTRIAL PROCESS	INPROCESS FUEL	RESIDUAL OIL	METAL MELTING	1000 GALLONS BURNED
3	90	004	06	INDUSTRIAL PROCESS	INPROCESS FUEL	RESIDUAL OIL	BRICK KILN/DRY	1000 GALLONS BURNED
3	90	004	07	INDUSTRIAL PROCESS	INPROCESS FUEL	RESIDUAL OIL	GYPSUM KILN/ETC	1000 GALLONS BURNED
3	90	004	99	INDUSTRIAL PROCESS	INPROCESS FUEL	RESIDUAL OIL	OTHER/NOT CLASIFD	1000 GALLONS BURNED
3	90	005	01	INDUSTRIAL PROCESS	INPROCESS FUEL	DISTILLATE OIL	ASPHALT DRYER	1000 GALLONS BURNED
3	90	005	02	INDUSTRIAL PROCESS	INPROCESS FUEL	DISTILLATE OIL	CEMENT KILN	1000 GALLONS BURNED
3	90	005	03	INDUSTRIAL PROCESS	INPROCESS FUEL	DISTILLATE OIL	LIME KILN	1000 GALLONS BURNED
3	90	005	04	INDUSTRIAL PROCESS	INPROCESS FUEL	DISTILLATE OIL	KAOLIN KILN	1000 GALLONS BURNED
3	90	005	05	INDUSTRIAL PROCESS	INPROCESS FUEL	DISTILLATE OIL	METAL MELTING	1000 GALLONS BURNED
3	90	005	06	INDUSTRIAL PROCESS	INPROCESS FUEL	DISTILLATE OIL	BRICK KILN/DRY	1000 GALLONS BURNED
3	90	005	07	INDUSTRIAL PROCESS	INPROCESS FUEL	DISTILLATE OIL	GYPSUM KILN/ETC	1000 GALLONS BURNED
3	90	005	99	INDUSTRIAL PROCESS	INPROCESS FUEL	DISTILLATE OIL	OTHER/NOT CLASIFD	1000 GALLONS BURNED
3	90	006	01	INDUSTRIAL PROCESS	INPROCESS FUEL	NATURAL GAS	ASPHALT DRYER	MILLION CUBIC FEET BURNED
3	90	006	02	INDUSTRIAL PROCESS	INPROCESS FUEL	NATURAL GAS	CEMENT KILN	MILLION CUBIC FEET BURNED
3	90	006	03	INDUSTRIAL PROCESS	INPROCESS FUEL	NATURAL GAS	LIME KILN	MILLION CUBIC FEET BURNED
3	90	006	04	INDUSTRIAL PROCESS	INPROCESS FUEL	NATURAL GAS	KAOLIN KILN	MILLION CUBIC FEET BURNED
3	90	006	05	INDUSTRIAL PROCESS	INPROCESS FUEL	NATURAL GAS	METAL MELTING	MILLION CUBIC FEET BURNED
3	90	006	06	INDUSTRIAL PROCESS	INPROCESS FUEL	NATURAL GAS	BRICK KILN/DRYS	MILLION CUBIC FEET BURNED
3	90	006	07	INDUSTRIAL PROCESS	INPROCESS FUEL	NATURAL GAS	GYPSUM KILN ETC	MILLION CUBIC FEET BURNED
3	90	006	99	INDUSTRIAL PROCESS	INPROCESS FUEL	NATURAL GAS	OTHER/NOT CLASIFD	MILLION CUBIC FEET BURNED
3	90	007	99	INDUSTRIAL PROCESS	INPROCESS FUEL	PROCESS GAS	OTHER/NOT CLASIFD	MILLION CUBIC FEET BURNED
3	90	008	99	INDUSTRIAL PROCESS	INPROCESS FUEL	COKE	OTHER/NOT CLASIFD	TONS
3	90	009	99	INDUSTRIAL PROCESS	INPROCESS FUEL	WOOD	OTHER/NOT CLASIFD	TONS BURNED
3	90	999	97	INDUSTRIAL PROCESS	INPROCESS FUEL	OTHER/NOT CLASIFD	SPECIFY IN REMARK	MILLION CUBIC FEET BURNED
3	90	999	98	INDUSTRIAL PROCESS	INPROCESS FUEL	OTHER/NOT CLASIFD	SPECIFY IN REMARK	1000 GALLONS BURNED
3	90	999	99	INDUSTRIAL PROCESS	INPROCESS FUEL	OTHER/NOT CLASIFD	SPECIFY IN REMARK	TONS BURNED
3	99	999	99	INDUSTRIAL PROCESS	OTHER/NOT CLASIFD	SPECIFY IN REMARK		TONS PROCESSED
4	01	001	01	POINT SC EVAP	CLEANING SOLVENT	DRYCLEANING	PERCHLOROETHYLENE	TONS CLOTHES CLEANED
4	01	001	02	POINT SC EVAP	CLEANING SOLVENT	DRYCLEANING	STODDARD	TONS CLOTHES CLEANED
4	01	002	01	POINT SC EVAP	CLEANING SOLVENT	DEGREASING	STODDARD	TONS SOLVENT USED
4	01	002	99	POINT SC EVAP	CLEANING SOLVENT	DEGREASING	OTHER/NOT CLASIFD	TONS SOLVENT USED
4	01	999	99	POINT SC EVAP	CLEANING SOLVENT	OTHER/NOT CLASIFD	SPECIFY IN REMARK	TONS SOLVENT USED
4	02	001	01	POINT SC EVAP	SURFACE COATING	PAINT	GENERAL	TONS COATING
4	02	003	01	POINT SC EVAP	SURFACE COATING	VARNISH/SHELLAC	GENERAL	TONS COATING
4	02	004	01	POINT SC EVAP	SURFACE COATING	LACQUER	GENERAL	TONS COATING
4	02	005	01	POINT SC EVAP	SURFACE COATING	ENAMEL	GENERAL	TONS COATING
4	02	006	01	POINT SC EVAP	SURFACE COATING	PRIMER	GENERAL	TONS COATING
4	02	999	99	POINT SC EVAP	SURFACE COATING	OTHER/NOT CLASIFD	SPECIFY IN REMARK	TONS COATING
4	03	001	01	POINT SC EVAP	PETROLEUM STG	FIXED ROOF	BREATHING-PRODUCT	1000 GALLONS STORAGE CAPACITY
4	03	001	02	POINT SC EVAP	PETROLEUM STG	FIXED ROOF	BREATHING CRUDE	1000 GALLONS STORAGE CAPACITY

TABLE 3. SAMPLE OF EMISSION FACTORS

POINT SC EVAP SURFACE COATING (CONTINUED)		POUNDS EMITTED PER UNIT					
		PART	SOX	NOX	HC	CO	UNITS
VARNESH/SHELLAC							
4-02-001-01	GENERAL				1,000.		TONS COATING
LAQUER							
4-02-004-01	GENERAL				1,540.		TONS COATING
ENAMEL							
4-02-005-01	GENERAL	0.	0.	0	840.	0.	TONS COATING
PRIMER							
4-02-006-01	GENERAL				1,320.		TONS COATING
COATING OVEN							
4-02-008-01	GENERAL						TONS COATING
SOLVENT							
4-02-009-01	GENERAL						TONS COATING
OTHER/NOT CLASIFD							
4-02-999-99	SPECIFY IN REMARK						TONS COATING
POINT SC EVAP	-PETROL PROD STG						
FIXED ROOF							
4-03-001-01	BREATH-GASOLINE	0.	0.	0.	80.1	0.	1000 GALLONS STORAGE CAPACITY
4-03-001-02	BREATH-CRUDE	0.	0.	0.	34.8	0.	1000 GALLONS STORAGE CAPACITY
4-03-001-03	WORKING-GASOLINE	0.	0.	0.	9.00	0.	1000 GALLONS THROUGHPUT
4-03-001-04	WORKING-CRUDE	0.	0.	0.	9.30	0.	1000 GALLONS THROUGHPUT
4-03-001-05	BREATH-JET FUEL	0.	0.	0.	45.2	0.	1000 GALLONS STORAGE CAPACITY
4-03-001-06	BREATH-KEROSENE	0.	0.	0.	13.1	0.	1000 GALLONS STORAGE CAPACITY
4-03-001-07	BREATH-DIST FUEL	0.	0.	0.	13.1	0.	1000 GALLONS STORAGE CAPACITY
4-03-001-08	BREATH-BENZENE	0.	0.	0.	18.3	0.	1000 GALLONS STORAGE CAPACITY
4-03-001-09	BREATH-CYCLOHEX	0.	0.	0.	20.8	0.	1000 GALLONS STORAGE CAPACITY
4-03-001-10	BREATH-CYCLOPENT	0.	0.	0.	58.4	0.	1000 GALLONS STORAGE CAPACITY
4-03-001-11	BREATH-HEPTANE	0.	0.	0.	18.3	0.	1000 GALLONS STORAGE CAPACITY
4-03-001-12	BREATH-HEXANE	0.	0.	0.	32.1	0.	1000 GALLONS STORAGE CAPACITY
4-03-001-13	BREATH-ISOOCTANE	0.	0.	0.	13.9	0.	1000 GALLONS STORAGE CAPACITY
4-03-001-14	BREATH-ISOPENTANE	0.	0.	0.	142.	0.	1000 GALLONS STORAGE CAPACITY
4-03-001-15	BREATH-PENTANE	0.	0.	0.	94.9	0.	1000 GALLONS STORAGE CAPACITY
4-03-001-16	BREATH-TOLUENE	0.	0.	0.	5.84	0.	1000 GALLONS STORAGE CAPACITY
4-03-001-50	WORKING-JET FUEL	0.	0.	0.	2.40	0.	1000 GALLONS THROUGHPUT
4-03-001-51	WORKING-KEROSENE	0.	0.	0.	1.09	0.	1000 GALLONS THROUGHPUT
4-03-001-52	WORKING-DIST FUEL	0.	0.	0.	1.00	0.	1000 GALLONS THROUGHPUT
4-03-001-53	WORKING-BENZENE	0.	0.	0.	2.00	0.	1000 GALLONS THROUGHPUT
4-03-001-54	WORKING-CYCLOHEX	0.	0.	0.	2.30	0.	1000 GALLONS THROUGHPUT
4-03-001-55	WORKING-CYCLOPENT	0.	0.	0.	6.40	0.	1000 GALLONS THROUGHPUT
4-03-001-56	WORKING-HEPTANE	0.	0.	0.	1.20	0.	1000 GALLONS THROUGHPUT
4-03-001-57	WORKING-HEXANE	0.	0.	0.	3.60	0.	1000 GALLONS THROUGHPUT
4-03-001-58	WORKING-ISOOCTANE	0.	0.	0.	1.50	0.	1000 GALLONS THROUGHPUT
4-03-001-59	WORKING-ISOPENT	0.	0.	0.	15.7	0.	1000 GALLONS THROUGHPUT
4-03-001-60	WORKING-PENTANE	0.	0.	0.	10.6	0.	1000 GALLONS THROUGHPUT
4-03-001-61	WORKING-TOLUENE	0.	0.	0.	0.64	0.	1000 GALLONS THROUGHPUT
FLOATING ROOF							
4-03-002-01	STAND STG-GASOLN	0.	0.	0.	12.0	0.	1000 GALLONS STORAGE CAPACITY
4-03-002-02	WORKING-PRODUCT				0.		1000 GALLONS THROUGHPUT
4-03-002-03	STAND STG-CRUDE	0.	0.	0.	10.6	0.	1000 GALLONS STORAGE CAPACITY
4-03-002-04	WORKING-CRUDE				0.		1000 GALLONS THROUGHPUT
4-03-002-05	STAND STG-JETFUEL	0.	0.	0.	4.38	0.	1000 GALLONS STORAGE CAPACITY
4-03-002-06	STAND STG-KEROSNE	0.	0.	0.	1.98	0.	1000 GALLONS STORAGE CAPACITY
4-03-002-07	STAND STG-DIST FL	0.	0.	0.	1.90	0.	1000 GALLONS STORAGE CAPACITY
4-03-002-08	STAND STG-BENZENE	0.	0.	0.	2.70	0.	1000 GALLONS STORAGE CAPACITY
4-03-002-09	STAND STG-CYCLHEX	0.	0.	0.	3.03	0.	1000 GALLONS STORAGE CAPACITY
4-03-002-10	STAND STG-CYCLPEN	0.	0.	0.	8.76	0.	1000 GALLONS STORAGE CAPACITY
4-03-002-11	STAND STG-HEPTANE	0.	0.	0.	1.64	0.	1000 GALLONS STORAGE CAPACITY
4-03-002-12	STAND STG-HEXANE	0.	0.	0.	4.75	0.	1000 GALLONS STORAGE CAPACITY
4-03-002-13	STAND STG-ISOCTN	0.	0.	0.	2.01	0.	1000 GALLONS STORAGE CAPACITY
4-03-002-14	STAND STG-ISOPENT	0.	0.	0.	20.8	0.	1000 GALLONS STORAGE CAPACITY
4-03-002-15	STAND STG-PENTANE	0.	0.	0.	13.9	0.	1000 GALLONS STORAGE CAPACITY
4-03-002-16	STAND STG-TOLUENE	0.	0.	0.	0.88	0.	1000 GALLONS STORAGE CAPACITY
VAR-VAPOR SPACE							
4-03-003-02	WORKING-GASOLINE	0.	0.	0.	10.2	0.	1000 GALLONS THROUGHPUT
4-03-003-03	WORKING-JET FUEL	0.	0.	0.	2.30	0.	1000 GALLONS THROUGHPUT
4-03-003-04	WORKING-KEROSENE	0.	0.	0.	1.00	0.	1000 GALLONS THROUGHPUT
4-03-003-05	WORKING-DIST FUEL	0.	0.	0.	1.00	0.	1000 GALLONS THROUGHPUT
4-03-003-06	WORKING-BENZENE	0.	0.	0.	2.30	0.	1000 GALLONS THROUGHPUT
4-03-003-07	WORKING-CYCLOHEX	0.	0.	0.	2.60	0.	1000 GALLONS THROUGHPUT
4-03-003-08	WORKING-CYCLOPENT	0.	0.	0.	7.20	0.	1000 GALLONS THROUGHPUT
4-03-003-09	WORKING-HEPTANE	0.	0.	0.	1.40	0.	1000 GALLONS THROUGHPUT
4-03-003-10	WORKING-HEXANE	0.	0.	0.	4.00	0.	1000 GALLONS THROUGHPUT
4-03-003-11	WORKING-ISOOCTANE	0.	0.	0.	1.70	0.	1000 GALLONS THROUGHPUT
4-03-003-12	WORKING-ISOPENT	0.	0.	0.	17.8	0.	1000 GALLONS THROUGHPUT
4-03-003-13	WORKING-PENTANE	0.	0.	0.	12.0	0.	1000 GALLONS THROUGHPUT
4-03-003-14	WORKING-TOLUENE	0.	0.	0.	0.73	0.	1000 GALLONS THROUGHPUT
OTHER/NOT CLASIFD							
4-03-999-99	SPECIFY IN REMARK						1000 GAL STORED

Hydrocarbon emissions from fuel combustion sources are part of the RAPS hourly emission inventory. Data for evaporative emissions, which account for approximately 40 percent of the point source hydrocarbon emission, are only gathered as part of inventory or production control and are presented as annual data.

Base data, such as storage capacity, throughput, production, consumption, etc., for the St. Louis Air Quality Control Region (AQCR-70) were obtained from 64 companies with emissions in excess of one ton per year. This represents about 450 points. Thirty-seven of the companies emit in excess of 100 tons per year, ten in excess of 10 tons per year, and seventeen in excess of one ton per year. Gas stations and dry cleaning establishments may emit greater than one ton per year hydrocarbons. However, they are included in the area sources inventory. Locations of the stacks, accurate to ten meters, were obtained from visiting plant sites and pinpointing the location of sources on U.S. Geological Survey maps. In addition, stack parameters and operating patterns were obtained from individual companies.

Emission patterns for hydrocarbon sources vary widely due to the variety of types of hydrocarbon sources. As mentioned before, emissions from combustion sources were received continuously as part of the RAPS Point Source Inventory, generally on an hourly basis. Hydrocarbon data from sources which produce or use coatings and solvents are accompanied with hourly use patterns based on working hours during a year. Evaporative emissions from petroleum storage are assumed to be generated on a continuous basis and are, therefore, spread equally throughout the year.

All of this information has been stored in the RAPS emission inventory data bank at EPA/RTP.

2.2 AREA SOURCES

Area sources of hydrocarbons include industrial area sources, residential and commercial sources, highway vehicles both as line and area sources, railroads and river vessels, airports, and off-highway mobile sources. All of the emissions from these sources have been spatially distributed into 1989 grids in accordance with the RAPS grid network (1).

Industrial area sources which are too small to be considered as point sources were determined by contacting individual companies and obtaining fuel consumption or throughput data. From these data, emissions were calculated using emission factors. These emissions were then assigned to the grid square in which the company was located. This category includes 53 companies.

Stationary residential and commercial sources include fuel combustion for heating, evaporative emissions from dry cleaning plants, surface coating operations and gasoline marketing, structural fires, and solid waste disposal. These emissions have been determined and distributed to each grid square according to residential and commercial land use.

Highway vehicle line source emissions have been determined and distributed over the AQCR according to the location of the line sources within the RAPS gridding system. Highway vehicle area sources have been determined as an off-shoot of the highway line sources and the emissions have been assigned to the appropriate grid square.

Airport emissions have been determined and distributed to those grids containing airports and in which flight operations take place, such as take-off and approach.

Off-highway mobile sources include motorcycles, lawn, garden and farm equipment, construction equipment, industrial equipment and outboard motors. The emissions from these sources have been distributed based on registrations; residential, farm and commercial land use; and navigable waters, respectively.

River vessel emissions were based on towboat traffic and determined primarily from records taken by the Corps of Engineers at Lock 27 near St. Louis and on emission factors derived for similar engines of the Coast Guard fleet and railroad locomotives.

Railroad fuel use and emissions were determined for two types of operations: line-haul operations and switch-yard activities. The former are described as line sources consisting of a series of links within the study area. Switch-yard operations utilize an area source concept.

For details of methodologies, the reader is referred to the reports listed in Section 2.0. The area source inventory also has been stored in the RAPS emission inventory data bank at EPA/RTP.

3.0 HYDROCARBON CLASSIFICATION

In order to make a breakdown of hydrocarbon emissions according to chemical structure, an appropriate compositional analysis must be applied to each category of emissions within the available total hydrocarbon inventory. Such an analysis has been applied by J. C. Trijonis and R. W. Arledge (2) to organic emissions in Los Angeles.

The work described in that study appears to be applicable to St. Louis with three major exceptions:

(1) Trijonis' "reactivity classes" do not coincide completely with the breakdown required for this report.

(2) Compositions of petroleum products and solvent usage may be appreciably different between St. Louis and Los Angeles.

(3) There are sources in St. Louis which are not considered in the Los Angeles study, such as coal combustion and coke ovens.

To make the information contained in the report applicable to the present study, the following modifications were made:

1. The Trijonis report is organized according to reactivity classes with 5-class reactivity categorization for organics. Each category contains groups of compounds by name, e.g. C_1-C_3 paraffins in Class I, mono and tertiary alkyl benzenes in Class II, C_4+ paraffins in Class III, primary and secondary alkyl benzenes in Class IV, and aliphatic olefins in Class IV.

All of the various organic emission sources in the Los Angeles area are discussed and analyzed to determine what chemical compounds are emitted. Each source is then tabulated to determine the extent of emissions in each reactivity class. The results are expressed in mole percent. In addition, the average molecular weights for each type of organic were determined and included in the report.

Since most of the source types exist both in Los Angeles and St. Louis, the report has been useful in classifying RAPS data. The tabulations have been reorganized by rearranging the chemical compounds into the broader classes of paraffins, olefins, aromatics, aldehydes and non-reactives. The non-reactives group includes all of the compounds in Class I of the Trijonis classification. The paraffins group includes C_4+ paraffins and alcohols, ketones, acetates and cellosolves. The aromatics group is composed of all aromatics with the exception of benzene, which is included with the non-reactives. The hydrocarbon classification tables developed for each type of source in the RAPS study area are included in the Appendix to this report.

The RAPS inventory presents emissions on a weight per unit time basis. For this reason, the classification of hydrocarbons was reported on a weight percent basis. This was accomplished by utilizing the molar percent tabulations and the average molecular weights presented in the Los Angeles study. The resulting tables are shown in Appendix A.

2. The composition of petroleum products in the St. Louis area was ascertained and adjustments were made in the tabulation of emissions arising from refinery operations, evaporative losses and automotive exhaust. These changes are discussed in detail in the text of the report.

3. Emissions from coal combustion and coke ovens were investigated and the results incorporated in this report.

3.1 POINT SOURCE INVENTORY

Once total hydrocarbon emissions were determined for each source, the hydrocarbon classification was applied to determine the non-reactives, paraffins, olefins, aromatics and aldehydes. The classification of hydrocarbon emissions from point sources is shown in Table 4.

3.1.1 Fuel Combustion

The nature of fuel combustion for power generation or steam production is similar at Los Angeles and at St. Louis; therefore, the same breakdown has been used here for oil and gas consumption. The hydrocarbon classification is shown in Table 1 of the Appendix.

TABLE 4. HYDROCARBON BREAKDOWN--POINT SOURCES

SCC	Weight %				
	Non-Reactive	Paraffins	Olefins	Aromatics	Aldehydes
1-XX-XXX-XX	66	10	9	5	10
2-XX-XXX-XX	66	10	9	5	10
3-01-018-99	0	0	0	100	0
3-01-026-99	0	0	0	100	0
3-01-999-99	0	0	0	100	0
3-03-003-01	83	1	13	3	0
3-03-003-02	83	1	13	3	0
3-03-003-03	83	1	13	3	0
3-06-001-02 to 3-06-001-09	66	10	9	5	10
3-06-002-01	5	95	0	0	0
3-06-004-01 to 3-06-008-05	5	74	15	6	0
3-90-XXX-XX	66	10	9	5	10
4-01-002-02	100	0	0	0	0
4-01-002-05	0	0	100	0	0
4-02-001-01	6	78	0	16	0
4-02-003-01	0	100	0	0	0
4-02-004-01	0	89	0	11	0
4-02-005-01	6	78	0	16	0
4-02-006-01	6	81	0	13	0
4-02-008-01	8	24	1	67	0
4-02-009-01	9	70	0	21	0
4-02-999-99	9	70	0	21	0
4-03-001-01	8	68	24	0	0
4-03-001-03	8	68	24	0	0
4-03-001-07	8	68	24	0	0
4-03-001-56	0	100	0	0	0
4-03-002-01	8	68	24	0	0
4-03-002-03	5	74	15	6	0
4-03-002-07	8	68	24	0	0
4-03-999-99	8	68	24	0	0
4-06-001-26	8	68	24	0	0
4-06-001-30	8	68	24	0	0
4-06-002-01	8	68	24	0	0
4-06-002-05	8	68	24	0	0
5-01-001-01	42	16	31	4	7

Hydrocarbon emissions from coal combustion were not studied by Trijonis, and the only literature data found on this subject referred only to total hydrocarbons and polynuclear hydrocarbons. Because of this lack of information, the classification reported for oil combustion was also used for emissions from coal combustion. This should be reasonably satisfactory considering the similarity of conditions of high temperature and residence time in a boiler, as well as the small amounts emitted. Two percent of the total hydrocarbons in the AQCR originates from boiler operations; moreover, most of it is methane.

3.1.2 Industrial Processes

Industrial sources of hydrocarbon emissions in AQCR 70 include some chemical manufacturing, coke production, refinery operations (which include fuel combustion covered previously), and evaporative emissions from degreasing operations, petroleum product storage and bulk marketing.

Emissions from chemical manufacturing in the St. Louis area occur primarily from manufacture of products used for plastic and rubber formulations. In all processes examined, the products are derivatives of benzene or phenol. The emissions are, therefore, entirely aromatics. This classification is shown in Table 2 of the Appendix.

Coke oven emissions result from several points in a coking plant including charging holes, pushing doors and many leaks. The best available sources (3-5) indicate that the composition of the emissions is similar to the coke oven gas which is produced in a coking plant. The composition of a typical coke oven gas is given in Table 5. This analysis has been reorganized and the hydrocarbon classification is included as Table 3 in the Appendix.

TABLE 5. COKE OVEN GAS ANALYSIS

Hydrogen Sulfide	0.7% by vol.	Ethylene	2.45% by vol.
Carbon Dioxide	1.7% by vol.	Propylene	0.34% by vol.
Nitrogen	0.9% by vol.	Propane	0.08% by vol.
Hydrogen	56.7% by vol.	Butylene	0.16% by vol.
Carbon Monoxide	5.7% by vol.	Butane	0.02% by vol.
Methane	29.6% by vol.	Acetylene	0.05% by vol.
Ethane	1.28% by vol.	Light Oil	0.65% by vol.

Refinery emissions arise from a variety of sources. Emissions from power house boilers and process heaters are included in the previous section on fuel combustion. Other emissions are from leaks or vents connected with transfers, drains, blow-downs, vacuum jets, compressors, valves, seals, and flanges. The Los Angeles study was very complete for refinery emissions. The operation of refineries is very similar at St. Louis and at Los Angeles. The basic difference is that crude oil in St. Louis is obtained from mid-continent and Arabian sources whereas the crude processed in Los Angeles is primarily from West Coast and Indonesian sources. Crude oil processed in California is generally of a much higher aromatic content, typically 20 to 35 percent versus 10 to 15 percent in the Midwest (6).

The Petroleum Chemicals Division of DuPont reports biannually on the characteristics of gasolines sampled across the country (7). Gasoline from St. Louis is not included in the survey, but Kansas City is, and the composition of gasoline in St. Louis is much like that in Kansas City (8). The average hydrocarbon analyses of gasolines from Los Angeles and Kansas City are given in Table 6. It can be seen that the aromatics are considerably higher in Los Angeles.

TABLE 6. DUPONT GASOLINE ANALYSIS

	Research Octane	Aromatics	Olefins	Saturates
		Percent		
Winter 1975-1976				
Los Angeles--leaded regular	93.2	27.0	7.0	65.0
unleaded regular	93.2	30.0	7.0	63.0
premium	98.6	26.0	4.0	70.0
Kansas City--leaded regular	92.9	14.5	13.0	72.5
unleaded regular	91.7	13.5	15.0	71.5
premium	98.8	14.0	7.5	78.5
Summer 1976				
Los Angeles--leaded regular	93.3	29.0	6.0	65.0
unleaded regular	93.5	35.0	7.0	58.0
premium	98.7	29.0	5.0	66.0
Kansas City--leaded regular	93.7	22.0	7.5	70.5
unleaded regular	91.5	21.0	12.0	67.0
premium	98.6	14.5	6.5	79.0

Combining the values for summer and winter as well as leaded and unleaded regular gasolines gives the values shown in Table 7. Since in 1975-1976 about 55 percent of the gasoline sold was regular, 45 percent premium, the averages were weighted by this proportion, which gave the values shown in columns 3 and 6 of Table 7. The percentage difference between Los Angeles and Kansas City is shown in the next column. These values were used to adjust gasoline related emissions and are reflected in Tables 4, 20 and 21 in Appendix A.

TABLE 7. AVERAGE COMPOSITION OF GASOLINES

	Los Angeles			Kansas City			
	1	2	3	4	5	6	7
	Regular %	Premium %	Weighted Average %	Regular %	Premium %	Weighted Average %	Percentage Difference
Aromatics	30.25	27.50	29.00	17.75	14.25	16.17	0.557
Olefins	6.75	4.50	5.75	11.88	7.00	9.68	1.686
Saturates	63.00	68.00	65.25	70.37	78.75	74.15	1.136

The classification of hydrocarbons emitted from catalytic crackers was determined by source test results and is included as Table 5 in the Appendix.

Degreasing operations are very straightforward. The solvents used are either trichloroethane or trichloroethylene. Trichloroethane is a partially halogenated paraffin, whereas trichloroethylene is a partially halogenated olefin. These sources are shown in the hydrocarbon classification scheme in Tables 6 and 7 in the Appendix.

Surface coating emissions occur from coating operations which include automobile and truck body and parts coating, applicances coating, and can manufacturing. A few of the companies have purely air-dried operations, but most of the coating operations involve a heat curing step. Each company involved in surface coating was evaluated to determine what percentage of the emitted hydrocarbons are evolved in the spray booths versus the curing ovens. This involved estimating the percentage of overspray and the time allowed for "flash-off" of a portion of the solvents used in formulation before the piece entered the curing oven. The values reported by Trijonis for heat treated coatings were applied to the hydrocarbons emitted in the curing ovens. The SCC codes differentiate between the types of surface coatings applied; i.e., lacquers, enamels, varnish, etc. Each type of coating was studied to determine the approximate hydrocarbon composition used in formulation (9, 10) and these compositions were used to classify the hydrocarbons emitted during the air drying part of the surface coating operation - the spray booths. The hydrocarbon classification for each type of surface coating included in the inventory is shown in Tables 8 through 12 in the Appendix.

Petroleum product storage and bulk marketing facilities have emissions which are typical of the vapors which exist over the liquids stored. All volatile petroleum products such as gasoline and crude oil are stored in floating-roof storage tanks. Emissions from these are solely due to leakage around the seals within the tanks. The other source of emissions is the filling of tank trucks and barges as vapors are displaced as the tank fills. The composition of the vapors accumulated over the gasoline approaches the equilibrium composition of gasoline vapor. The hydrocarbon classifications for emissions from gasoline storage tanks are shown in Table 13 of the

Appendix.

3.2 AREA SOURCES

The classification of hydrocarbon emissions from area sources is shown in Table 8.

River vessels and railroads are assumed to have diesel engines which produce all of the hydrocarbon emissions. Emissions from diesel engines were studied extensively by Battelle Labs (11). The results should be applicable to St. Louis. The classification of hydrocarbons used here is the same as for diesel engines presented in Table 22 in the Appendix.

Airport emissions include aircraft operations, exhaust emissions from service vehicles and evaporative emissions from fuel handling. Hydrocarbon emissions are distributed 79 percent, 13 percent and 8 percent, respectively, to these sources (12). Lambert International and Scott Air Force Base contributed 96.2 percent of the total hydrocarbons. Since, within the bounds of this study, it was not possible to classify the hydrocarbons from all airports individually, the hydrocarbon classification was based on the operations at Lambert International and Scott Air Force Base.

Table 9 shows the classification of emissions for each of the hydrocarbon sources and the weighted average for the airport. The complete classification of these emissions is presented in Table 14 of the Appendix. The aircraft emissions are based on the assumption of originating entirely from jet engines; 98 percent of the aircraft emissions occur during the taxi and idle modes of operation. The service vehicle emissions are assumed to be the same as automotive exhaust emissions. Fuel handling emissions are the same as the evaporative emissions from storing jet fuel.

TABLE 9. AIRPORT HYDROCARBON EMISSIONS

TYPE	% OF TOTAL	NON-REACTIVE	PARAFFINS	OLEFINS	AROMATICS	ALDEHYDES
Aircraft	79	11	44	27	15	3
Service Vehicle	13	12	47	15	26	0
Fuel Handling	8	0	70	5	25	0
Weighted Average		10	47	24	17	2

TABLE 8. HYDROCARBON BREAKDOWN--AREA SOURCES

	Weight %				
	Non-Reactive	Paraffins	Olefins	Aromatics	Aldehydes
River Vessels	3	53	12	12	20
Railroads	3	53	12	12	20
Residential and Commercial Fuel Combustion	66	10	9	5	10
Evaporative					
Surface Coating					
Missouri	6	57	0	37	0
Illinois	9	70	0	21	0
Gasoline Marketing	8	68	24	0	0
Dry Cleaning	76	23	0	1	0
Structural Fires	42	16	31	4	7
Solid Waste Disposal	42	16	31	4	7
Stationary Industrial	26	52	3	16	3
Airports	10	47	24	17	2
Highway					
Light Duty Vehicle					
Exhaust	11	48	21	20	0
Evaporative	4	60	20	16	0
Heavy Duty - Gas					
Exhaust	11	48	21	20	0
Evaporative	4	60	20	16	0
Heavy Duty - Diesel					
Exhaust	3	53	12	12	20
Off-Highway Sources					
Motorcycles	12	47	15	26	0
Lawn & Garden	12	47	15	26	0
Farm Equipment	8	49	14	21	8
Construction Equip.	7	50	13	18	11
Industrial Equip.	10	49	14	23	4
Outboard Motors	12	47	15	26	0

Stationary residential and commercial fuel combustion sources include combustion of coal, oil, natural gas, and liquified petroleum gas. For these emissions the same classification used with point source fuel combustion was applied (Table 1, Appendix).

Evaporative hydrocarbons from surface coating include emissions due to the solvent content of retail paints. Illinois has a state regulation restricting photochemically reactive solvents which is very similar to Los Angeles APCD Rule 66 (13). Trijonis' report includes a table of the national average solvent composition which is given in Table 10. According to Mr. Raymond Connor of the National Paint and Coating Association (14), this table of values is still the best available information. The State of Missouri does not have a hydrocarbon regulation similar to Illinois; therefore, the data in Table 10, column 3, were used for the Missouri portion of the hydrocarbons from surface coating. The composition in the last column of Table 10 was used for the Illinois portion of the hydrocarbons. The individual classifications of hydrocarbons in each state are presented in Tables 15 and 16 in the Appendix.

Evaporative hydrocarbons from service stations are generated from filling the underground storage tanks at service stations and from filling automobile tanks. The volume of these emissions is considered as being split equally from the filling of the underground tanks and automobile tanks (15). The DuPont analyses of gasoline in Kansas City and Los Angeles have been used to modify the emissions classification.

Evaporative hydrocarbons from dry cleaning operations are the result of using cleaning solvents which are either perchloroethylene or petroleum based solvents. Based on a 1974 study in St. Louis city, the usage if 76 weight percent perchloroethylene and 23 weight percent petroleum based solvents. Table 11 gives the hydrocarbon compositions from each of these solvent types and the weighted average which is used for classifying the cumulative emissions in the AQCR. This classification is presented in further detail in Table 17 in the Appendix.

TABLE 10. COMPOSITION OF SURFACE COATING SOLVENTS

	ACTUAL OR ESTIMATED MOLECULAR WEIGHT	1972 ANNUAL NATIONWIDE CONSUMPTION; lbs. PER CAPITA	COMPOSITION OF SOLVENTS NATIONWIDE; MOLE %† OF TOTAL HYDROCARBONS	REACTION REQUIRED BY LAC APCD - RULE 66	SUBSTITUTION OF OTHER COMPOUNDS	ESTIMATED COMPOSITION OF COATING SOLVENTS IN THE LOS ANGELES AREA; MOLE %† OF TOTAL HYDROCARBONS
ALIPHATIC HYDROCARBONS						
Mineral spirits, regular, low odor	86* (C_6)	2.005	14.9		Unknown mixture of C_6* paraffins	Unknown mixture of C_6* paraffins
Mineral spirits, odorless	86* (C_6)	0.396	2.9			
Kerosene	142 (C_{10})	0.053	0.3			
Mineral spirits, heavy, coal-oil	86* (C_6)	0.165	1.2			
Other aliphatic hydrocarbons	86 (C_6)	1.142	8.5		8.5	36.7
		3.751	27.8			
AROMATIC & NAPTHENIC HYDROCARBONS						0.3
Benzene	78 (-)	0.033	0.3			0.7
•Toluene (Rule 66-K-3)	92 (-)	1.802	12.1	3.4		6.0
•Tylene (Rule 66-K-2)	106 (-)	2.277	13.6	7.8		2.1
Naphtha, high flash	138*(C_{10})	0.462	2.1			1.1
•Other aromatics (Rule 66-K-2)	120*(C_9)	0.986	2.6	1.5		2.3
Napthenic Hydrocarbons	140*(C_{10})	1.505	2.3	12.7		20.5
			33.2			
TERPENIC HYDROCARBONS						0.1
(Pine oil & turpentine)	136*(C_{10})	0.033	0.1			0.1
		0.033				
ALCOHOLS (MONOHYDRIC)						3.8
Methyl Alcohol ("methanol")	32 (-)	0.041	1.8		2.8	1.6
Ethyl alcohol (inc. all denatured grades)	46 (-)	0.072	1.8			2.8
Propyl alcohol (n. & iso.)	60 (-)	0.264	2.8			3.3
n butyl alcohol	74 (-)	0.378	3.3			0.3
Other butyl alcohols	74 (-)	0.033	0.3			0.8
Other monohydric alcohols	102*(C_6)	0.134	0.5		2.8	12.8
		0.972	10.8			
GLYCOLS & DERIVATIVES						4.0
Glycols	90*(C_4)	0.568	4.0			0.5
Glycol ethers (Cellosolves)	90*(C_4)	0.627	4.5			0.5
		1.195	8.5			
KETONES & ESTERS						9.6
Acetone (di-methyl ketone)	58 (-)	0.642	7.1		2.5	6.2
Methyl ethyl ketone (M.E.K.)	72 (-)	0.690	6.2			1.3
•Methyl isobutyl ketone (Rule 66-K-3)	100 (-)	0.275	1.8	0.5		0.3
•Other ketones (Rule 66-K-3)	120*(C_8)	0.082	0.4	0.1		0.2
Ethyl acetate	88 (-)	0.029	0.2			0.2
Isopropyl acetate	102 (-)	0.020	0.2			1.7
Normal butyl acetate	116 (-)	0.311	1.7			0.5
Other esters	100*(C_6)	0.295	0.5	0.6	2.5	20.4
		2.262	18.5			
CHLORINATED SOLVENTS						0.4
Methylene chloride	84 (-)	0.048	0.4			0.1
•Tri-chloro ethylene (Rule 66-K-3)	136 (-)	0.034	0.2	0.1		0.5
Other chlorinated solvents	150*(C_6Cl_2)	0.006	0.1	0.1		2.0
		0.088	0.7			
OTHER SOLVENTS & DILUENTS						0.6
C_{10} + Cycloparaffins	140*(C_{10})	0.278	0.6			0.6
C_{10} + Paraffins	142*(C_{10})		0.6			1.2
		0.278	1.2			
		14.181	100	13.6	13.6	100

* Estimated or assumed

• Use of these compounds limited by Los Angeles County Air Pollution Control District Rule 66-K

† Mole % assumed to equal volume %

Reproduced from best available copy.

TABLE 11. DRY CLEANING HYDROCARBON EMISSIONS

SOLVENT	NON-REACTIVE	PARAFFINS	OLEFINS	AROMATICS	ALDEHYDES
Perchloroethylene	100	0	0	0	0
Petroleum Based	0	94	0	6	0
Weighted Average	76	23	0	1	0

Hydrocarbon emissions from structural fires and solid waste disposal are the last type of residential and commercial sources. The only data available for this source are reported by Trijonis and are reflected in Table 8. The detailed classification of hydrocarbons from waste incineration is shown in Table 18 in the Appendix.

Emissions from stationary industrial sources include a variety of types of activities. The best approximation of these sources indicates that 70 percent consists of air dried surface coating and 30 percent of combustion (16). The classification in Table 8 reflects these percentages. A detailed classification of hydrocarbons from this combination of sources is shown in Table 19 in the Appendix.

As stated earlier, gasoline in Los Angeles has a much higher aromatic content than gasoline in St. Louis. The effect of higher aromatic content in gasoline on exhaust emissions has been heavily studied. A numerical relationship has been expressed by Wigg, et al (17), which states that there is a linear relationship between aromatic hydrocarbon emissions and fuel aromatic content and an inverse relationship between olefin emissions and fuel aromatic content. This relationship is reported to be in relatively good agreement with other studies on the same subject (18, 19). The equations which were developed in this study are:

$$\text{Exhaust (aromatic - benzene), \%} = 0.49 \text{ fuel aromatic, \%}$$

and

$$\text{Exhaust olefin \%} = 39-(0.30 \text{ fuel aromatic}), \%$$

These equations and the DuPont analyses have been used to modify the composition of hydrocarbons in automotive exhaust. The exhaust composition thus derived is also in agreement with results reported by Kopczynski, et al,

in a planning study in preparation for the RAPS project (20).

Evaporative hydrocarbon emissions from automobiles are comprised of emissions from fuel tank breathing and the evaporation of gasoline from the carburetor fuel bowl. These emissions have been determined by modifying the values reported by Trijonis by decreasing the aromatic content by 44 percent and increasing the olefin content.

The composition of hydrocarbons from automobile exhaust and evaporative emissions are given in Table 8. The composition of the exhaust and evaporative emissions of heavy duty gasoline powered trucks have been assumed to be identical to those for light duty vehicles since there is no fundamental difference between the engines and fuels used. The composition of the exhaust emissions for heavy duty diesel powered trucks are classified in Table 8. These are the same as those used for railroads which use diesel engines. Evaporative emissions from diesel engines are considered negligible. The classifications of exhaust and evaporative hydrocarbon emissions are presented in Tables 20, 21 and 22 in the Appendix.

Off-highway mobile sources are comprised of a mix of gasoline and diesel engines (22). Motorcycles, lawn and garden, and outboards are all gasoline engines. Farm equipment is 61.9 percent gasoline powered, construction equipment is 44 percent gasoline powered, and industrial equipment is 78 percent gasoline powered. The exhaust hydrocarbon classification data in Table 8 expresses these percentages. The exhaust emissions from gasoline engines are the same as the previously discussed automotive emissions, and the exhaust emissions from diesel engines are the same as the previously discussed diesel truck engines. The reclassifications of the hydrocarbons from the groups of combined gasoline and diesel engines are presented in Tables 23, 24, and 25 in the Appendix.

4.0 SUMMARY

A detailed inventory of organic emissions has been developed for the St. Louis AQCR. The inventory has been incorporated into the RAPS data base and is stored on EPA's Univac 1110 computer at Research Triangle Park, North Carolina.

The inventory consists of a listing of all industrial point source emissions in excess of one ton per year, a listing of stationary area sources such as gasoline marketing and dry cleaning operations, and a compilation of mobile sources including surface transportation, railroad, river vessels, airports and off-highway mobile sources.

Emission data are available for each source category, either as total hydrocarbons or broken down into five structural categories: paraffins, olefins, aromatics, aldehydes and non-reactives. Appropriate factors were developed for the St. Louis area and applied to the hydrocarbon emission data. These classification factors are also stored on the Univac computer. As a consequence, an emission inventory for the five categories of organics is now available for the St. Louis AQCR. A summary of the total emission broken down into the five structural categories is shown in Table 12.

TABLE 12. SUMMARY OF TOTAL ORGANIC EMISSIONS INVENTORY BY CLASS

SOURCE CATEGORY	ANNUAL EMISSIONS, TONS/YR. NON REACTIVE	PARAFFINS	OLEFINS	AROMATICS	ALDEHYDES	TOTALS
Point Sources						
Fuel Combustion	1,793	272	245	136	271	2,717
Chem. Manufacturing	-	-	-	6,702	-	6,702
Primary Metals	1,941	23	305	70	-	2,339
Refinery Operations	358	5,299	1,074	430	-	7,161
Surface Coatings	843	15,593	-	4,636	-	21,072
Petroleum Storage & Marketing	597	5,070	1,790	-	-	7,457
Solid Waste Disposal	57	22	42	5	10	136
Miscellaneous	12	-	12	-	-	
Point Source Totals						47,610
Area Sources						
Industrial Area Sources	29	57	3	18	3	110
Residential & Commercial	14,923	2,261	2,035	1,130	2,261	22,610
Vehicles, Line Sources, Exhaust	8,093	35,314	15,450	14,714	-	73,570
Vehicles, Line Sources, Evap.	1,021	15,321	5,107	4,086	-	25,535
Vehicles, Line Sources, Diesel	40	708	160	160	267	1,335
Vehicles, Area Sources	1,257	6,283	2,010	2,890	125	12,565
Railroads	127	2,237	506	506	844	4,220
River Vessels	28	498	113	113	188	940
Airports	146	686	350	248	30	1,460
Off-Highway Mobile	1,628	7,977	2,279	3,744	652	16,280
Gas Marketing	1,092	9,282	3,276	-	-	13,650
Dry Cleaning	490	148	-	7	-	645
Surface Coating	255	2,271	-	1,231	-	3,757
Area Source Totals						176,677
GRAND TOTAL						224,287

REFERENCES

1. Haws, Richard C., Paddock, Richard E., and Masser, Charles C., The Regional Air Pollution Study (RAPS) Grid System. EPA-450/3-76-021, Research Triangle Park, North Carolina, December 1975.

2. Trijonis, J. C. and K. W. Arledge. Utility of Reactivity Criteria in Organic Emission Control Strategies for Los Angeles. EPA Contract Number 68-02-1735, TRW Environmental Services, December 1975.

3. National Research Council Committee. Chemistry of Coal Utilization. Edited by Lowry, 1945, Vol. III.

4. Smith, William M. Evaluation of Coke Oven Emissions. Presented at 78th General Meeting of American Iron and Steel Institute, May 28, 1970.

5. United Nations Economic Committee--Europe. Air Pollution by Coking Plants. 1968.

6. Sachanen, A. N. The Chemical Constituents of Petroleum. Reinhold, New York, 1945.

7. E. I. DuPont de Nemours and Company, Inc., Petroleum Chemicals Division. Road Octane Survey. Winter 1975-1976 and Summer 1976.

8. Private communication, Ed Sullivan, Amoco Oil Company, Wood River, Illinois, March 21, 1977.

9. Danielson, John A. (ed.) Air Pollution Engineering Manual. AP-40, U.S. Environmental Protection Agency. May 1973.

10. Gaynes, Norman I. Formulation of Organic Coatings. 1967.

11. Spicer, C. W. and A. Levy. The Photochemical Smog Reactivity of Diesel Exhaust Organics. Report to the Coordinating Research Council from Battelle Columbus Laboratories, May 1975.

12. Patterson, R. M., R. D. Wang and F. A. Record. Airport Emission Inventory Methodology. EPA Contract Number 68-02-0041, GCA Corporation, December 1974.

13. Private communication, Mike Elbl, Illinois Environmental Protection Agency, Collinsville, Illinois, March 24, 1977.

14. Private communication, Raymond J. Connor, Assistant Technical Director, National Paint and Coating Association, Washington, D.C., March 24, 1977.

15. Holden, R. E. and W. E. Zegel. Residential and Commercial Area Source Emission Inventory Methodology for the Regional Air Pollution Study. EPA-450/3-75-078, Environmental Science and Engineering, Inc., September 1975.

16. Littman, F. E. and Kevin Isam. Stationary Industrial Area Source Emission Inventory. Rockwell International, EPA Contract No. 68-02-2093 T0108D, July 1976.

17. Wigg, E. E., R. J. Campion and W. L. Petersen. The Effect of Fuel Hydrocarbon Composition on Exhaust Hydrocarbon and Oxygenate Emissions. Society of Automotive Engineers Report Number 720251, presented to the Automotive Engineering Congress, Detroit, Michigan, January 10-14, 1972.

18. Dishart, K. T. and W. C. Harris. The Effect of Gasoline Hydrocarbon Composition on Automotive Exhaust Emission. Proceedings at American Petroleum Institute, Division of Refineries, 1968, Vol. 48, pp. 612-642.

19. Eccleston, B. H. and R. W. Hurn. Comparative Emissions from Some Leaded and Prototype Lead-Free Automobile Fuels. Bureau of Mines, RI Number 7390, May 1970.

20. Kopczynski, S. L., W. A. Lonneman, T. Winfield and R. Seila. Gaseous Pollutants in St. Louis and Other Cities. J. Air Pollution Control Association, 25:251, 1975.

21. Compilation of Air Pollutant Emission Factors. AP-42, U.S. Environmental Protection Agency, Supplement 5, December 1975.

22. Hare, Charles T. Methodology for Estimating Emissions from Off-Highway Mobile Sources for the RAPS Program. EPA 450/3-75-002, October 1974.

APPENDIX A

RAPS Hydrocarbon Classification for Types of Sources

TABLE A-1

RAPS HYDROCARBON CLASSIFICATION

FUEL COMBUSTION

Aver. Mol. Wt. 25

T&A 3-13 & A-5

NON-REACTIVES	mol %	wt %	PARAFFINS	mol %	wt %	OLEFINS	mol %	wt %	AROMATICS	mol %	wt %	ALDEHYDES	mol %	wt %
C_1 - C_3 paraffins	85	61	C_4^+ paraffins	3	10	Aliphatic olefins	3	9	Prim.& Sec.-alkyl benzenes	1	5	Aliphatic aldehydes	3	10
Acetylene	5	5												
		66			10			9			5			10

TABLE A-2

RAPS HYDROCARBON CLASSIFICATION

ORGANIC CHEMICAL MANUFACTURING

Plasticizers, Rubber Chemicals, Pesticides, etc.

NON-REACTIVES			PARAFFINS			OLEFINS			AROMATICS			ALDEHYDES		
	mol %	wt %		mol %	wt %		mol %	wt %		mol %	wt %		mol %	wt %
									Benzene derivatives	100	100			
											100			

TABLE A-3

RAPS HYDROCARBON CLASSIFICATION

COKE OVENS

Aver. Mol. Wt. 35

NON-REACTIVES	mol %	wt %	PARAFFFINS	mol %	wt %	OLEFINS	mol %	wt %	AROMATICS	mol %	wt %	ALDEHYDES	mol %	wt %
C_1 - C_3 paraffins	89.4	77	C_4^+ paraffins	0.1	1	Aliphatic olefins	8.6	13	Prim.& Sec.-alkyl benzenes	0.5	3			
Benzene	1.4	6												
Acetylene	0.1	<1												
		83			1			13			3			0

TABLE A-4

RAPS HYDROCARBON CLASSIFICATION

REFINERY OPERATIONS

Aver. Mol. Wt. 93

T&A 3-6 & A-2 (Adjusted)

NON-REACTIVES	mol %	wt %	PARAFFINS	mol %	wt %	OLEFINS	mol %	wt %	AROMATICS	mol %	wt %	ALDEHYDES	mol %	wt %
C_1 - C_3 Paraffins	6	1.9	C_4^+ paraffins	67	72	Aliphatic olefins	14	13	Prim.& Sec.-alkyl benzenes	3	4			
Acetylene	2	.6							Dialkyl benzenes	5	6			
Benzene	3	2.5												
		5			72			13			10			
		5			74*			15*			6*			

* Adjusted for Midwestern crudes

TABLE A-5

RAPS HYDROCARBON CLASSIFICATION

CATALYTIC CRACKER REGENERATOR

Aver. Mol. Wt. 120

NON-REACTIVES			PARAFFINS			OLEFINS			AROMATICS			ALDEHYDES		
	mol %	wt %		mol %	wt %		mol %	wt %		mol %	wt %		mol %	wt %
C_1 - C_3 paraffins	2	1	C_4^+ paraffins	90	95									
Acetylene	3	1												
Benzene	5	3												
		5			95									

TABLE A-6

RAPS HYDROCARBON CLASSIFICATION

DEGREASING - Trichloroethane

NON-REACTIVES			PARAFFINS			OLEFINS			AROMATICS			ALDEHYDES		
	mol %	wt %		mol %	wt %		mol %	wt %		mol %	wt %		mol %	wt %
Partially halogenated paraffin	100	100												
		100												

TABLE A-7

RAPS HYDROCARBON CLASSIFICATION

DEGREASING - Trichloroethylene

NON-REACTIVES			PARAFFINS			OLEFINS			AROMATICS			ALDEHYDES		
	mol %	wt %		mol %	wt %		mol %	wt %		mol %	wt %		mol %	wt %
						Partially halogenated olefin	100	100						
								100						

TABLE A-8

RAPS HYDROCARBON CLASSIFICATION

SURFACE COATING - AIR DRIED - Paint, Enamel

Aver. Mol. Wt. 100

NON-REACTIVES	mol %	wt %	PARAFFFINS	mol %	wt %	OLEFINS	mol %	wt %	AROMATICS	mol %	wt %	ALDEHYDES	mol %	wt %
Acetone	7	4	C_4^+ paraffins	41	41				Prim. & Sec.-alkyl benzenes	6	7			
Methanol	2	1	Cycloparaffins	6	9				Dialkyl benzenes	4	7			
Partially halogenated paraffins	1	1	N-alkyl ketones	7	6				Tri & tetra - alkyl benzenes	1	2			
			Prim. & Sec.-alkyl acetates	5	5									
			Branched alkyl ketones	3	2									
			Prim. & Sec.-alkyl alcohols	13	11									
			Cellosolves	4	4									
		6			78			0			16			0

TABLE A-9

RAPS HYDROCARBON CLASSIFICATION

SURFACE COATING - AIR DRIED - Lacquer

Aver. Mol. Wt. 70

NON-REACTIVES	mol %	wt %	PARAFFINS	mol %	wt %	OLEFINS	mol %	wt %	AROMATICS	mol %	wt %	ALDEHYDES	mol %	wt %
			C_4^+ paraffins	11	12				Aromatics	12	11			
			Alcohols	16	16									
			Ketones	26	25									
			Esters	29	30									
			Ethers	6	6									
		0			89			0			11			0

TABLE A-10

RAPS HYDROCARBON CLASSIFICATION

SURFACE COATING - AIR DRIED - Varnish

Aver. Mol. Wt. 70

NON-REACTIVES			PARAFFINS			OLEFINS			AROMATICS			ALDEHYDES		
	mol %	wt %		mol %	wt %		mol %	wt %		mol %	wt %		mol %	wt %
			Ketones	97	97									
			Ethers	3	3									
		0			100			0			0			0

TABLE A-11

RAPS HYDROCARBON CLASSIFICATION

SURFACE COATING - AIR DRIED - Primers

Aver. Mol. Wt. 82

NON-REACTIVES	mol %	wt %	PARAFFFINS	mol %	wt %	OLEFINS	mol %	wt %	AROMATICS	mol %	wt %	ALDEHYDES	mol %	wt %
Acetone	6	4	C_4^+ paraffins	47	47				Aromatics	10	13			
Methanol	4	2	Alcohols	13	13									
			Ketones	11	11									
			Esters	7	8									
			Ethers	2	2									
		6			81			0			13			0

TABLE A-12

RAPS HYDROCARBON CLASSIFICATION

Aver. Mol. Wt. 82

T&A 3-17 & A-7

SURFACE COATING - HEAT CURED - General

NON-REACTIVES	mol %	wt %	PARAFFINS	mol %	wt %	OLEFINS	mol %	wt %	AROMATICS	mol %	wt %	ALDEHYDES	mol %	wt %
C_1 - C_3 paraffins	20	8	C_4^+ paraffins	28	24	Aliphatic olefins	2	1	Prim. & Sec. - alkyl benzenes	35	45			
									Dialkyl benzenes	15	22			
		8			24			1			67			0

TABLE A-13

RAPS HYDROCARBON CLASSIFICATION

PETROLEUM STORAGE TANKS - Gasoline

Aver. Mol. Wt. 58

T&A 3-8 & A-3

NON-REACTIVES			PARAFFINS			OLEFINS			AROMATICS			ALDEHYDES		
	mol %	wt %		mol %	wt %		mol %	wt %		mol %	wt %		mol %	wt %
C_1 - C_3 paraffins	18	8	C_4^+ paraffins	59	67	Aliphatic olefins	22	24						
			Cycloparaffins	1	1									
		8			68			24			0			0

TABLE A-14

RAPS HYDROCARBON CLASSIFICATION

AIRPORTS

NON-REACTIVES	mol %	wt %	PARAFFINS	mol %	wt %	OLEFINS	mol %	wt %	AROMATICS	mol %	wt %	ALDEHYDES	mol %	wt %
C_1 - C_3 paraffins		10	C_4+ paraffins		47	Aliphatic olefins		24	Alkyl benzenes		17	Aliphatic aldehydes		2
Benzene			Napthenes											
Acetylene														
		10			47			24			17			2

TABLE A-15

RAPS HYDROCARBON CLASSIFICATION

SURFACE COATING - AIR DRIED - General

Missouri

NON-REACTIVES	mol %	wt %	PARAFFINS	mol %	wt %	OLEFINS	mol %	wt %	AROMATICS	mol %	wt %	ALDEHYDES	mol %	wt %
Acetone	7	4	C_4^+ paraffins	30	28				Prim.& Sec.- alkyl benzenes	12	14			
Methanol	2	1	Cycloparaffins	2	3				Dialkyl benzenes	14	18			
Partially halogenated paraffins	1	1	N-alkyl ketones	6	5				Tri & tetra - alkyl benzenes	3	5			
			Prim.& Sec.- alkyl acetates	3	4									
			Branched alkyl ketones	2	2									
			Prim.& Sec.- alkyl alcohols	14	11									
			Cellosolves	4	4									
		6			57			0			37			0

TABLE A-16

RAPS HYDROCARBON CLASSIFICATION

SURFACE COATING - AIR DRIED - General

Illinois

Aver. Mol. Wt. 87

T&A 3-19 & A-9

NON-REACTIVES	mol %	wt %	PARAFFFINS	mol %	wt %	OLEFINS	mol %	wt %	AROMATICS	mol %	wt %	ALDEHYDES	mol %	wt %
Acetone	10	7	C_4^+ paraffins	37	37				Prim.& Sec.-alkyl benzenes	9	11			
Methanol	4	1	Cycloparaffins	5	8				Dialkyl benzenes	6	8			
Partially halogenated paraffins	1	1	N-alkyl ketones	6	5				Tri & tetra - alkyl benzenes	1	2			
			Prim.& Sec.-alkyl acetates	3	4									
			Branched alkyl ketones	2	2									
			Prim.& Sec.-alkyl alcohols	12	10									
			Cellosolves	4	4									
		9			70			0			21			0

TABLE A-17

RAPS HYDROCARBON CLASSIFICATION

DRY CLEANING

NON-REACTIVES	mol %	wt %	PARAFFINS	mol %	wt %	OLEFINS	mol %	wt %	AROMATICS	mol %	wt %	ALDEHYDES	mol %	wt %
Perhalo-genated hydrocarbons	71	76	C_4^+ paraffins	9	10				Prim., Sec.& dialkyl benzenes	1	0.6			
			Cycloparaffins	18	13				Tri & tetra - alkyl benzenes	1	0.4			
		76			23			0			1			0

TABLE A-18

RAPS HYDROCARBON CLASSIFICATION

WASTE INCINERATION

Aver. Mol. Wt. 33

T&A 3-15 & A-6

NON-REACTIVES	mol %	wt %	PARAFFINS	mol %	wt %	OLEFINS	mol %	wt %	AROMATICS	mol %	wt %	ALDEHYDES	mol %	wt %
C_1 - C_3 paraffins	62	32	C_4^+ paraffins	3	8	Aliphatic olefins	13	27	Dialkyl benzenes	1	4	Aliphatic aldehydes	3	7
Acetylene	8	6	N-alkyl ketones	2	4	Alkyl acetylenes	2	4						
Methanol	4	4	Prim.& Sec.- alkyl alcohols	2	4									
		42			16			31			4			7

TABLE A-19

RAPS HYDROCARBON CLASSIFICATION

STATIONERY INDUSTRIAL

Aver. Mol. Wt. 86

NON-REACTIVES	mol %	wt %	PARAFFINS	mol %	wt %	OLEFINS	mol %	wt %	AROMATICS	mol %	wt %	ALDEHYDES	mol %	wt %
C_1 - C_3 paraffins	75	18	C_4^+ paraffins	27	29	Aliphatic olefins	1	3	Prim.& Sec.-alkyl benzenes	7	9	Aliphatic aldehydes	1	3
Acetylene	1	1	Cycloparaffins	3	6				Dialkyl benzenes	4	6			
Acetone	7	5	N-alkyl ketones	4	3				Tri & tetra - alkyl benzenes	1	1			
Methanol	3	1	Prim.& Sec.-alkyl acetates	2	3									
Partially helogenated paraffins	1	1	Branched alkyl ketones	1	1									
			Prim.& Sec.-alkyl alcohols	8	7									
			Cellosolves	3	3									
		26			52			3			16			3

TABLE A-20

RAPS HYDROCARBON CLASSIFICATION

LIGHT DUTY VEHICLE and HEAVY DUTY-

Gas Exhaust

Aver. Mol. Wt. 69

T&A 3-41, 3-46 & A-18, A-20 *

NON-REACTIVES	mol %	wt %	PARAFFINS	mol %	wt %	OLEFINS	mol %	wt %	AROMATICS	mol %	wt %	ALDEHYDES	mol %	wt %
C_1 - C_3 paraffins	14	4	C_4^+ paraffins	30	42	Aliphatic olefins	20	12	Prim.& Sec.- alkyl benzenes	6	8			
Acetylene	11	4							Dialkyl benzenes	13	22			
Benzene	3	3							Tri & tetra - alkyl benzenes	3	5			
					42			12			35			
		11			48*			21*			20*			0

* Adjusted for Midwestern crudes

TABLE A-21

RAPS HYDROCARBON CLASSIFICATION

LIGHT DUTY VEHICLE and HEAVY DUTY-

Gas Evaporative

Aver. Mol. Wt. 91

T&A 3-47 & A-21 *

NON-REACTIVES	mol %	wt %	PARAFFFINS	mol %	wt %	OLEFINS	mol %	wt %	AROMATICS	mol %	wt %	ALDEHYDES	mol %	wt %
C_1 - C_3 paraffins	1	1	C_4^+ paraffins	57	55	Aliphatic olefins	13	12	Prim.& Sec.- alkyl benzenes	9	9			
Benzene	4	3	Cycloparaffins	1	1				Dialkyl benzenes	12	15			
									Tri & tetra - alkyl benzenes	3	4			
		4			56			12			28			
		4			60*			20*			16*			

* Adjusted for Midwestern crudes

TABLE A-22

RAPS HYDROCARBON CLASSIFICATION

DIESEL ENGINE EXHAUST

Aver. Mol. Wt. 89

T&A 3-52 & A-24

NON-REACTIVES	mol %	wt %	PARAFFINS	mol %	wt %	OLEFINS	mol %	wt %	AROMATICS	mol %	wt %	ALDEHYDES	mol %	wt %
C_1 - C_3 paraffins	11	2	C_4^+ paraffins	24	53	Aliphatic olefins	27	12	Prim.& Sec.-alkyl benzenes	1	2	Aliphatic aldehydes	30	20
Acetylene	2	1							Dialkyl benzenes	5	10			
		3			53			12			12			20

TABLE A-23

RAPS HYDROCARBON CLASSIFICATION

OFF HIGHWAY - Farm Equipment

NON-REACTIVES	mol %	wt %	PARAFFINS	mol %	wt	OLEFINS	mol	wt	AROMATICS	mol	wt	ALDEHYDES	mol	wt
C_1 - C_3 paraffins	13	3	C_4^+ paraffins	28	49	Aliphatic olefins	25	14	Prim.& Sec.- alkyl benzenes	3	5	Aliphatic aldehydes	11	8
Acetylene	8	3							Dialkyl benzenes	9	15			
Benzene	2	2							Tri & tetra - alkyl benzenes	1	1			
		8			49			14			21			8

TABLE A-24

RAPS HYDROCARBON CLASSIFICATION

OFF HIGHWAY - Construction Equipment

NON-REACTIVES	mol %	wt %	PARAFFINS	mol %	wt %	OLEFINS	mol %	wt %	AROMATICS	mol %	wt %	ALDEHYDES	mol %	wt %
C_1 - C_3 paraffins	12	3	C_4^+ paraffins	28	50	Aliphatic olefins	25	13	Prim. & Sec. - alkyl benzenes	2	4	Aliphatic aldehydes	17	11
Acetylene	6	2							Dialkyl benzenes	8	13			
Benzene	1	2							Tri & tetra - alkyl benzenes	1	1			
		7			50			13			18			11

TABLE A-25

RAPS HYDROCARBON CLASSIFICATION

OFF HIGHWAY - Industrial Equipment

NON-REACTIVES	mol %	wt %	PARAFFINS	mol %	wt %	OLEFINS	mol %	wt %	AROMATICS	mol %	wt %	ALDEHYDES	mol %	wt %
C_1 - C_3 paraffins	13	4	C_{4^+} paraffins	30	49	Aliphatic olefins	25	14	Prim. & Sec. - alkyl benzenes	3	5	Aliphatic aldehydes	7	4
Acetylene	9	3							Dialkyl benzenes	10	16			
Benzene	2	3							Tri & tetra - alkyl benzenes	1	2			
		10			49			14			23			4

TECHNICAL REPORT DATA
(Please read Instructions on the reverse before completing)

1. REPORT NO.	2	3. RECIPIENT'S ACCESSION NO.
EPA-600/4-78-028		

4. TITLE AND SUBTITLE	5. REPORT DATE
REGIONAL AIR POLLUTION STUDY Point and Area Source Organic Emission Inventory	June 1978
	6. PERFORMING ORGANIZATION CODE
7. AUTHOR(S) R.W. Griscom	8. PERFORMING ORGANIZATION REPORT NO.
9. PERFORMING ORGANIZATION NAME AND ADDRESS Rockwell International Air Monitoring Center 11640 Administration Drive Creve Coeur, MO 63141	10. PROGRAM ELEMENT NO. 1AA603 AA-09 (FY-77) 11. CONTRACT/GRANT NO. 68-02-2093 Task Order 108 I
12. SPONSORING AGENCY NAME AND ADDRESS Environmental Sciences Research Laboratory - RTP, NC Office of Research and Development U.S. Environmental Protection Agency Research Triangle Park, NC 27711	13. TYPE OF REPORT AND PERIOD COVERED Final 14. SPONSORING AGENCY CODE EPA/600/09

15. SUPPLEMENTARY NOTES

16. ABSTRACT

An inventory of organic emissions from stationary and mobile sources has been assembled for the St. Louis Air Quality Control Region. The inventory covers point and area sources for process, combustion and evaporative emissions. A breakdown into five categories had been assigned to each source type. The categories are (1) paraffins, (2) olefins, (3) aromatics, (4) aldehydes, and (5) non-reactives. This report describes how this classification has been determined for hydrocarbon emissions in the St. Louis AQCR and provides sufficient reference data to derive alternative schemes as required. The breakdown was made part of the RAPS Emission Inventory System, which is stored on the EPA's Univac computer at Research Triangle Park, N.C.

17. KEY WORDS AND DOCUMENT ANALYSIS

a. DESCRIPTORS	b. IDENTIFIERS/OPEN ENDED TERMS	c. COSATI Field/Group
*Air pollution *Organic compounds *Emission *Environmental surveys *Sources	St. Louis, MO	13 B 07 C 05 J

18. DISTRIBUTION STATEMENT	19. SECURITY CLASS (This Report)	21. NO. OF PAGES
RELEASE TO PUBLIC	UNCLASSIFIED	58
	20. SECURITY CLASS (This page)	22. PRICE
	UNCLASSIFIED	A04-A01

EPA Form 2220-1 (Rev. 4-77) PREVIOUS EDITION IS OBSOLETE